



Mini-guard Series - Line-Interactive UPS (500-2000VA)

Main Features

- Advanced digital control technique
- Streamline, colorful appearance design
- Comprehensive net equipment protection
- Green idea environmental design
- Flexible and practical cold start function
- Wide voltage range for intellectual regulating (SMART AVR)
- Intelligent power management (optional)



Application: PC, SOHO, office, small device.

Main Specification:

MODEL		UPS500	UPS700/ UPS700L	UPS1000/ UPS1000L	UPS1600/ UPS1600L	UPS2000/ UPS2000L	SUPS500	SUPS700	SUPS1000
INPUT	Voltage(Vac)	140~280 / 90~145					190~265		
	Frequency (Hz)	50/60 ± 10%							
OUTPUT	Power(VA/W)	500/300	700/420	1000/600	1600/960	2000/1200	500/300	700/420	1000/600
	Voltage(Vac)	220/230±10% ; 110/120±10% (on battery mode)					220/230±10%(on battery mode)		
	Frequency(Hz)	Synchronizing with the Utility on AC mode, and 50±0.5% or 60 ± 0. 5% on battery mode							
	Transfer Time	2-6ms							
	Waveform	Square wave					Pure sine wave		
BATTERY	Voltage (Vdc)	12	12	12/24	36	36/48	12	24	24
	BATT Type	1×7Ah	1×7Ah/ External	2×7Ah/ External	3×7Ah/ External	3×9Ah/ External	1×7Ah	2×7Ah	
	Charger Current(A)Max	1	1/ 8	1/ 6	1/ 5	1/ 5	1		
OTHER	Communication Interface	RS232, RJ11 / RJ45 (USB or SNMP adapter is optional)					USB, RJ11 / RJ45		
	Display	LCD display show status of AC input, inverter, low battery, overload and battery capacity, or LED indicators show status of AC input, inverter, low battery, overload							
	Dimension (W×D×H)	90×325×165/ 120×395×220		120×395×220	156×450×220		120×250×170	120×380×170	
	Weight(kg)	5	5.5/8	11/8	17/13	18/14	5	8	9

Telephone: 07 3390 4622

Specialist Export Services Pty Ltd, 20 Miller Street, Murarrie, QLD, 4172 Facsimile: 07 3390 6600

www.exportservices.com.au